

**Tohaco car transporter with 2 axles: AA227/4520 and AA235/4520**

**AA227/4520 and AA235/4520 fitted with fully electronic airsuspension.**

For the regular user, who is looking for the highest reachable quality. Exceptionally comfortable, safe and with an entirely lowerable bed. No more ramps needed!

The airsuspension system is mounted completely underneath the vehicle. Equipped with an 18-bar quality compressor with air dryer, electronic operating system and automatic level control. Heavy duty 12V, 75Ah AGM battery. Easy to operate with push buttons mounted in the drawbar. Only works with fully connected 13-pin plug!

-Available with a gross mass of 2700kg or 3500kg.

-To your choice with an 18mm plywood floor, 19mm floor made of aluminum profiles, galvanized steel perforated floor, or aluminum tread plate deck overlay on plywood floor.

Optional:

-Equipped with a second compressor to reach the ride height or exit height even faster.

-Remote control to be able of loading cars single-handed.

Specifications of the airsuspension system:
4 bellows
4 shock absorbers
Polyamide air hoses
Stainless steel couplings
Custom wiring harness
Only with fully connected 13-pin Jaeger plug
Air suspension system mounted under the trailer
12v, 75Ah AGM battery
2 height sensors
Electronic level control and driving height adjustment
Easy to control push buttons in the drawbar
Compressor 12V, 18bar with air dryer
Air tank 10 liter
ASCU (Air Suspension Control Unit)
Plug for external battery charger
Emergency valves
Mechanical lowering protection



## Pricelist Tohaco car transporters AA227/4520 and AA235/4520 per 01-05-2024

Type	Bed size	Gross weight	Load capacity	Retail price excluding
AA227/4520	458x200cm	2700kg	ca. 1905kg	€ 9.895,00
AA235/4520	458x200cm	3500kg	ca. 2680kg	€ 10.750,00

Delivery abroad with COC (Certificate of Conformity)

Length bed is length of mounted floor + length of steel ramp!

Delivery ex works, without possible transport costs (see our website for a list of dealers)

Optional, additional price when new	Retail price excluding
Battery charger Ctek MXS 5.0T with Tohaco plug	€ 135,00
Spare wheel mounted	€ 186,00
Remote control	€ 355,00
2nd compressor with extra 5-liter air tank	€ 895,00
Aluminum floor, additional price	At request
Aluminum tread plate deck overlay on plywood floor, screwed and glued	€ 1.200,00
Galvanized steel perforated floor with plywood middle track	€ 1.675,00
Galvanized steel perforated floor with alu. tread plate middle track	€ 2.050,00
Galvanized steel perforated floor 3 tracks	€ 2.275,00
Wheel stop for perforated floor left or right, apiece	€ 92,00
Ratchet strap for securing over the wheel in perforated floor	€ 34,00
"Y" Ratchet strap for car transport	€ 31,00
Alloy rims, additional price apiece	€ 155,00
Double Lock Fixed Lock 'C' SCM, approved by insurers in the Netherlands, mounted	€ 205,00
LED lighting	€ 325,00
Winch manual 1200kg including 8m <sup>1</sup> winch belt and winch support	€ 475,00
Winch manual 1450kg including 8m <sup>1</sup> winch belt and winch support	€ 530,00
Winch electric 2000kg with remote control and winch support	€ 995,00
Winch electric 2200kg with remote control and winch support	€ 1.275,00

### Technical specifications:

Make	Tohaco	
Type	AA227/4520	AA235/4520
Chassis	Hot-dip galvanized	
Suspension	Independent, air suspension	
Bed	Fully lowerable for loading and unloading. Ramp angle approx. 4°	
Number of wheels, tire size, rim size	4, 195/50 RC 13C, steel rims 6Jx13H2 5 holes	
Brakes	Knott, mechanic	
Overrun brake	Knott KF27	Knott KF35
Length	5970mm	
Height	1000mm	
Width	2540mm	
Bed length, steel ramp included	4550mm	
Bed width	2000mm	
Bed height	360mm	
Mass roadworthy (depending on equipment)	795kg	820kg
Gross weight	2700kg	3500kg
Load capacity	ca. 1905kg	ca. 2680kg
Maximum nose weight	100kg	
Bed	18mm birch plywood with anti-slip coating	
Jockey wheel	Automatic retractable, galvanized, full rubber wheel	
Plug	13-pin Jaeger plug necessary	
Air suspension system	Electronic	
Ride height and level control	Automatic by sensor	
Air tank	10 liters	
Bellows	4	
Shock absorbers	4	
Compressor	12V, 18 bar, with air dryer	
Valve block	In compressorbox	
ASCU (Air Suspension Control Unit)	In compressorbox	
Emergency valves for rear axle	2, left and right	
Mechanical lowering protection	Against unintentional lowering the bed	
Battery	12V, 75Ah, AGM semi traction	
Plug for external battery charger	Tohaco	
Wiring harness	Tohaco	
Wiring box	Tohaco	
Lighting system	Aspock	
Anchor points	Multiple anchor points in rail, left, right and front	
License plate holder	Collapsible, suited with led-light	