

Tohaco Motorcycle transporter
available with 3 possible airsuspension systems:

MO116/2515, top model, fitted with full electronic air suspension system.

For the regular user, who is looking for the highest reachable quality.
 The airsuspension system is mounted completely underneath the vehicle. Equipped with an 18-bar quality compressor with air dryer, electronic operating system and automatic level control. Heavy duty 12V, 70Ah AGM battery. Easy to operate with push buttons mounted in the drawbar. Only works with fully connected 13-pin plug!

MO116/2515TV, fitted with electronic compressor and manual operated valves, mounted in a stainless-steel box between the drawbar.

Equipped with a 10-bar compressor and a 12V, 34Ah AGM battery. Simple to operate with manual valves. Fitted with a 13-pin plug.

MO116/2515ECO, basic model, fitted with a car tire valve and 2 twist taps.

The air springs are supplied with air by use of external air supply, such as a portable compressor.
 By operating the twist taps you can raise and lower the bed, and correct weight differences between left and right. With a 7- or 13-pin plug.

Specifications of all three air suspension systems	MO116/2515	MO116/2515TV	MO116/2515EC
2 bellows	V	V	V
2 shock absorbers	V	V	V
Polyamide air hoses	V	V	V
Stainless steel couplings	V	V	V
Custom wiring harness	V	V	V
Mechanical lowering protection	V	V	V
Only with fully connected 13-pin Jaeger plug	V		
Air suspension system mounted under the trailer	V		
12V, 75Ah AGM battery	V		
2 height sensors	V		
Electronic level control and driving height adjustment	V		
Easy to control push buttons in the drawbar	V		
Compressor 12V, 18bar with air dryer	V		
ASCU (Air Suspension Control Unit)	V		
2 emergency valves	V	V	
Plug for external battery charger	V	V	
Stainless steel box for the airsuspension system		V	
12V, 34Ah AGM battery, mounted under the bed		V	
Compressor 12V, 10bar		V	
2 operating valves, left/right		V	
13-pin Jaeger plug		V	
12V overload protector		V	
Ride height indicators		V	V
Manual level control		V	V
2 twist taps for manual level control, left/right			V
Air valve for adding air with an external (portable) compressor/pump, switch for air outlet			V
Controls in the front of the chassis			V
13-pin or 7-pin plug			V



Pricelist Tohaco motorcycle transporters per 01-05-2024

Type	Bed size	Gross weight	Load capacity	Retail price excluding VAT
MO116/2515	280x150cm	1600kg	ca. 1180 kg	€ 6.550,00
MO116/2515TV	280x150cm	1600kg	ca. 1195 kg	€ 5.850,00
MO116/2515EC	280x150cm	1600kg	ca. 1205 kg	€ 4.850,00

Delivery abroad with COC (Certificate of Conformity)

Length bed is length wooden or aluminum floor + steel ramp!

Delivery ex works, without possible transport costs (see our website for a list of dealers)

Optional, additional price when new	Retail price excluding
Tohaco motorcycle support, mounting to chassis, wheel size 15"-19", 90-130mm wide	€ 138,00
Motorcycle support for floor mounting, wheel size 15"-19", 90-130mm wide	€ 132,00
Motorcycle support for floor mounting, wheel size 15"-21", 90-200mm wide	€ 189,00
Motorcycle support freely movable, wheel size 15"-19", 90-130mm wide	€ 156,00
Motorcycle support freely movable, wheel size 15"-21", 90-200mm wide	€ 224,00
Spare wheel mounted with support (MO)	€ 151,00
Alloy rims, additional price, apiece	€ 155,00
Ratchet strap endless 1500kg/25x1500mm	€ 14,00
Ratchet strap with S-hooks 1000kg/25x2200mm	€ 17,00
Ratchet kit for one motorcycle, 1 endless strap, 2 straps with S-hooks	€ 40,00
Tyrefix ratchet strap for strapping motorcycles over the wheel	€ 88,00
Tyrefix basic for use with separate ratchet straps	€ 65,00
Battery charger Ctek MXS 5.0T with Tohaco plug adapter	€ 135,00
Double Lock Fixed type C/WAK SCM, coupling lock, mounting included	€ 205,00
LED lighting	€ 325,00

Technical specifications:

Make	Tohaco		
Type	MO116/2515	MO116/2515TV	MO116/2515EC
Chassis	Hot-dip galvanized		
Suspension	Independent, air suspension		
Bed	Fully lowerable for loading and unloading. Ramp angle approx. 5°		
Number of wheels, tire size, rim size	2, 195/50 RC 13C, steel rims 6Jx13H2 5 holes		
Brakes	Knott, mechanic		
Overrun brake	Knott KF20		
Length	4100mm		
Height	1000mm		
Width	2120mm		
Bed length, steel ramp included	2800mm		
Bed width	1500mm		
Bed height	360mm		
Mass roadworthy (depending on equipment)	420kg	405kg	395kg
Gross weight	1600kg		
Load capacity	ca. 1180kg	ca. 1195kg	ca. 1205kg
Maximum nose weight	100kg		
Bed	18mm birch plywood with anti-slip coating		
Jockey wheel	Automatic retractable, galvanized, full rubber wheel		
Plug	13-pin Jaeger plug necessary	13-pin Jaeger plug	13-pin Jaeger plug
Air suspension system	Electronic	Electric manually	External pump or compressor
Ride height and level control	Automatic by sensor	Manually, ride height indicator	Manually, ride height indicator
Bellows	2		
Shock absorbers	2		
Compressor	12V, 18bar, with moist filter	12V, 10bar	n.a.
Valve block	In compressorbox	n.a.	n.a.
ASCU (Air Suspension Control Unit)	In compressorbox	n.a.	n.a.
Emergency valves	2, left and right		
Mechanical lowering protection	Against unintentional lowering the bed		
Battery	12V, 75Ah, AGM semi traction	12V, 34Ah, AGM semi traction	n.a.
Plug for external battery charger	Tohaco		
Wiring harness	Tohaco		
Wiring box	Tohaco	n.a.	n.a.
Lighting system	Aspock		
Anchor points	Multiple anchor points left, right, middle and front		
License plate holder	Collapsible, suited with led-light		