

Tohaco machine transporters with 2 axles

Machine transporters fitted with fully electronic airsuspension

For the regular user, who is looking for the highest reachable quality. Exceptionally comfortable, safe and with an entirely lowerable bed. No more ramps needed!

The airsuspension system is mounted completely underneath the vehicle. Equipped with an 18-bar quality compressor with air dryer, electronic operating system and automatic level control. Heavy duty 12V, 75Ah AGM battery. Easy to operate with push buttons mounted in the drawbar. Only works with fully connected 13-pin plug!

Available three different sizes and in two different weight classes, with a gross mass of 2700kg or 3500kg.

Specifications of the airsuspension system:
4 bellows
4 shock absorbers
Polyamide air hoses
Stainless steel couplings
Custom wiring harness
Only with fully connected 13-pin Jaeger plug
Air suspension system mounted under the trailer
12V, 75Ah AGM battery
2 height sensors
Electronic level control and driving height adjustment
Easy to control push buttons in the drawbar
Compressor 12V, 18bar with air dryer
Air tank 10 liter
ASCU (Air Suspension Control Unit)
Plug for external battery charger
Emergency valves
Mechanical lowering protection



Pricelist Tohaco machine transporters per 01-05-2024

Type	Bed size	Gross weight	Load capacity	Retail price excluding VAT		
MA227/3715	370x150cm	2700kg	ca. 2051kg	€ 9.495,00		
MA235/3715	370x150cm	3500kg	ca. 2826kg	€ 10.295,00		
MA227/3917	397x170cm	2700kg	ca. 2000kg	€ 9.495,00		
MA235/3917	397x170cm	3500kg	ca. 2775kg	€ 10.295,00		
MA227/4518	459x180cm	2700kg	ca. 1935kg	€ 9.895,00		
MA235/4518	459x180cm	3500kg	ca. 2710kg	€ 10.750,00		
Delivery abroad with COC (Certificate of Conformity)						
Length bed is length of mounted floor + length of steel ramp!						
Delivery ex works, without possible transport costs (see our website for a list of dealers)						
Optional, additional price when new				Retail price excluding VAT		
Battery charger Ctek MXS 5.0T with Tohaco plug adapter				€ 135,00		
Spare wheel mounted with support				€ 186,00		
Double Lock Fixed type C/WAK SCM, coupling lock, mounting included				€ 205,00		
2nd compressor with extra 5-liter air tank				€ 895,00		
Remote control				€ 355,00		
LED lighting				€ 325,00		
Aluminum tread plate deck overlay on plywood floor, screwed and glued				€ 1.200,00		
Front rack				€ 295,00		
Storage box for mounting on front rack, plastic				€ 145,00		
Winch manual 1200kg including 8m ¹ winch belt and winch support				€ 475,00		
Winch manual 1450kg including 8m ¹ winch belt and winch support				€ 530,00		
Winch electric 2000kg with remote control and winch support				€ 995,00		
Winch electric 2200kg with remote control and winch support				€ 1.275,00		
Hood, see full pricelist, depending on model and version, price starting at				€ 3.100,00		
Enclosed body, see full pricelist, depending on model and version, price starting at				€ 7.925,00		
Technical specifications:						
Make	Tohaco					
Type	MA227/3715	MA235/3715	MA227/3917	MA235/3917	MA227/4518	MA235/4518
Chassis	Hot-dip galvanized					
Suspension	Independent, air suspension					
Bed	Fully lowerable for loading and unloading. Ramp angle approx. 4°					
Number of wheels, tire size, rim size	4, 195/50 R13 C, steel rims 6Jx13H2 5 holes					
Brakes	Knott, mechanic					
Overrun brake	Knott KF27	Knott KF35	Knott KF27	Knott KF35	Knott KF27	Knott KF35
Length	5060mm	5060mm	5330mm	5330mm	5960mm	5960mm
Height	950mm					
Width	2080mm	2080mm	2280mm	2280mm	2400mm	2400mm
Bed length, steel ramp included	3700mm	3700mm	3966mm	3966mm	4590mm	4590mm
Bed width	1500mm	1500mm	1700mm	1700mm	1800mm	1800mm
Bed height	360mm					
Mass roadworthy (depending on equipment)	649kg	674kg	700kg	725kg	765kg	790kg
Gross weight	2700kg	3500kg	2700kg	3500kg	2700kg	3500kg
Load capacity	ca. 2051kg	ca. 2826kg	ca. 2000kg	ca. 2775kg	ca. 1935kg	ca. 2710kg
Maximum nose weight	100kg					
Bed	18mm birch plywood with anti-slip coating					
Jockey wheel	Automatic retractable, galvanized, full rubber wheel					
Plug	13-pin Jaeger plug necessary					
Air suspension system	Electronic					
Ride height and level control	Automatic by sensor					
Air tank	10 liters					
Bellows	4					
Shock absorbers	4					
Compressor	12V, 18 bar, with air dryer					
Valve block	In compressorbox					
ASCU (Air Suspension Control Unit)	In compressorbox					
Emergency valves for rear axle	2, left and right					
Mechanical lowering protection	Against unintentional lowering the bed					
Battery	12V, 75Ah, AGM semi traction					
Plug for external battery charger	Tohaco					
Wiring harness and wiring box	Tohaco					
Lighting system	Aspock					
Anchor points	Multiple anchor points in rail, left, right and front					
License plate holder	Collapsible, suited with led-light					