

Tohaco Motorcycle transporter, available with 3 possible airsuspension systems:

MO116/2515, top model, fitted with full electronic air suspension system.

For the regular user, who is looking for the highest reachable quality.

The airsuspension system is mounted completely underneath the vehicle. Equipped with an 18-bar quality compressor with air dryer, electronic operating system and automatic level control. Heavy duty 12v 70Ah traction battery. Easy to operate with push buttons mounted in the drawbar. Only works with fully connected 13-pin plug!

MO116/2515TV, fitted with electronic compressor and manual operated valves, mounted in a stainless-steel box between the drawbar.

Fitted with a 10-bar compressor and a 12v 34Ah traction battery. Simple to operate with manual valves. Fitted with a 13-pin plug, and with reservation, with our special Tohaco 7/13 adapter also compatible with a 7-pin plug.

MO116/2515ECO, basic model, fitted with a car tire valve and 2 twist taps.

The air springs are supplied with air by use of external air supply, such as a portable compressor.

By operating the twist taps you can raise and lower the bed, and correct weight differences between left and right. 7 or 13-pin plug.

Specifications of all three air suspension systems	MO116/2515	MO116/2515TV	MO116/2515ECO
2 bellows	X	X	X
2 adjustable shock absorbers	X	X	X
Polyamide air hoses	X	X	X
Stainless steel couplings	X	X	X
Custom wiring harness	X	X	X
Only with fully connected 13-pin Jaeger plug	X		
Air suspension system mounted under the trailer	X		
12v traction battery 70Ah	X		
2 height sensors	X		
Electronic level control and driving height adjustment	X		
Easy to control push buttons in the drawbar	X		
Compressor 12v 18 bar with air dryer	X		
ASCU (Air Suspension Control Unit)	X		
2 Emergency valves	X	X	
Plug for external battery charger	X	X	
Stainless steel box for the air suspension system		X	
12v traction battery 34Ah, mounted under the bed		X	
Compressor 12v 10bar		X	
2 operating valves, left/right		X	
13-pin plug or (with Tohaco adapter) 7-pin plug		X	
12V overload protection		X	
Manual level control		X	X
Ride height indicators		X	X
2 twist taps for manual level control, left/right			X
Air valve for adding air with an external (portable) compressor/pump			X
Controls in the front of the chassis			X
13-pin or 7-pin plug			X



Pricelist Tohaco motorcycle transporters: per 01-05-2018:

Type	Bed size	Gross weight	Load capacity	Retail price excluding VAT	
MO116/2515	280x150cm	1600 kg	ca. 1140 kg	€ 4.706,61	
MO116/2515TV	280x150cm	1600 kg	ca. 1190 kg	€ 4.210,74	
MO116/2515Eco	280x150cm	1600 kg	ca. 1210 kg	€ 3.384,30	
Delivery abroad with COC (Certificate of Conformity) Length bed is length wooden or aluminum floor + steel ramp! Delivery ex works, without possible transport costs					
Optional, additional price when new				Retail price excluding VAT	
Motorcycle support with wheel lever		Mounted with ringbolts		€109,92	
Spare wheel mounted with support				€128,10	
Alloy rims (N) additional price apiece				€132,23	
Ratchet strap endless 1500kg/1,5m		For 1 motorcycle		€8,43	
Ratchet strap with hooks 1500kg/3,00m				€14,46	
Ratchet strap set 1x endless, 2x with hooks				€32,23	
Tyrefix strap for motorcycles				€74,30	
Black&Decker ASI 500 Portable compressor		For MO116/2515Eco		€125,00	
Double Lock Fixed Lock ,C' SCM		Approved by insurers in Holland		€125,62	
Double Lock Fixed Lock ,C' SCM		Approved by insurers in Holland		Montage included €172,73	
Tohaco-Trailer adapter 7/13 (TV only)				€24,71	
See our general price list for all options					

Motorrادtrailer Tohaco MO116/2515 Technische Spezifikationen

Make	TOHACO		
	MO116/2515EV	MO116/2515TV	MO116/2515ECO
Type	Hot-dip galvanized		
Chassis	Hot-dip galvanized		
Suspension	Independent, air suspension		
Bed	Fully lowerable for loading and unloading. Ramp angle approx. 4°.		
Number of wheels, size tire, size rim	2, 195/50 RC 13C, steel rims 6Jx13H2 5 holes		
Brakes	Knott, mechanic		
Overrun brake	KF20		
Length	4100mm		
Height	1000mm		
Width	2120mm		
Bed length, steel ramp included	2800mm		
Bed width	1500mm		
Bed height	360mm		
Gross weight	1600kg		
Mass roadworthy (depending on equipment)	ca. 440 kg	ca. 405 kg	ca. 395 kg
Load capacity	ca. 1160 kg	ca. 1195 kg	ca. 1205 kg
Maximum nose weight	100 kg		
Bed	18mm birch plywood with anti-slip coating		
Jockey wheel	Automatic retractable, galvanized, full rubber wheel		
Plug	13-pin Jaeger plug necessary	13-pin plug, or with special Tohaco adapter 7-pin possible	7- or 13-pin plug
Air suspension system	Electronic automatic	Electronic manual	External air source
Ride height and level control	Automatic	Manual with ride height indicator	Manual with ride height indicator
Bellows	2		
Shock absorbers	2		
Compressor	12V, 18-Bar	12V, 10-Bar	n.a.
ASCU (Air Suspension Control Unit)	in compressorbox	n.a.	n.a.
Valve block	in compressorbox	n.a.	n.a.
Battery	12V 70Ah traction	12V 34Ah traction	n.a.
Wiring harness	Tohaco		
Wiring box	Tohaco	n.a.	n.a.
Lighting system	Aspock		
Anchor points	Multiple anchor points left, right, front and in the middle		
License plate holder	Collapsible, suited with led-light		