

**Tohaco car transporter with 1 axle: AA116/3518(TV) and AA118/3518(TV)**

**AA116/3518 and AA118/3518 fitted with fully electronic airsuspension.**

For the regular user, who is looking for the highest reachable quality. Exceptionally comfortable, safe and with an entirely lowerable bed. No more ramps needed!

The airsuspension system is mounted completely underneath the vehicle. Equipped with an 18-bar quality compressor with air dryer, electronic operating system and automatic level control. Heavy duty 12V, 75Ah AGM battery. Easy to operate with push buttons mounted in the drawbar. Only works with fully connected 13-pin plug!

- Available with a gross mass of 1600 kg or 1800 kg.
- To your choice with an 18mm plywood floor, or 19mm floor made of aluminum profiles.

Optional:

- Equipped with a 5 liter air tank to reach the ride height or exit height even faster.
- Remote control to be able of loading cars single-handed.

**AA116/3518TV and AA118/3518TV, fitted with complete airsuspension system mounted in a stainless-steel box between the drawbar.**

Fitted with a 10-bar compressor and a 12V, 34Ah traction battery. Simple to operate with manual valves. Fitted with a 13-pin plug.

- Available with a gross mass of 1600 kg or 1800 kg.
- To your choice with an 18mm plywood floor, or 19mm floor made of aluminum profiles.

The specifications for the air suspension:	AA116/3518 AA118/3518	AA116/3518TV AA118/3518TV
2 bellows	V	V
2 shock absorbers	V	V
Polyamide air hoses	V	V
Stainless steel couplings	V	V
Custom wiring harness	V	V
Plug for external battery charger	V	V
Emergency valves	V	V
Mechanical lowering protection	V	V
Only with fully connected 13-pin Jaeger plug	V	
Air suspension system mounted under the trailer	V	
12V, 75Ah AGM battery	V	
2 height sensors	V	
Electronic level control and driving height adjustment	V	
Easy to control push buttons in the drawbar	V	
Compressor 12V, 18bar with air dryer	V	
ASCU (Air Suspension Control Unit)	V	
Air tank 5 liter	Optional	
Remote control	Optional	
Stainless steel box for the airsuspension system		V
12V,34Ah AGM battery, mounted under the bed		V
Compressor 12V, 10bar		V
2 operating valves, left/right		V
13-pin Jaeger plug		V
12V overload protector		V
Ride height indicators		V



## Pricelist Tohaco car transporters AA116/3518(TV) and AA118/3518(TV) per 01-04-2022

Type	Bed size	Gross weight	Load capacity	Retail price excluding VAT
AA116/3518	350x180cm	1600kg	ca. 1116kg	€ 6.995,00
AA118/3518	350x180cm	1800kg	ca. 1299kg	€ 7.195,00
AA116/3518TV	350x180cm	1600kg	ca. 1130kg	€ 6.295,00
AA118/3518TV	350x180cm	1800kg	ca. 1312kg	€ 6.495,00
Delivery abroad with COC (Certificate of Conformity)				
Length bed is length of mounted floor + length of steel ramp!				
Delivery ex works, without possible transport costs (see our website for a list of dealers)				
Optional, additional price when new				Retail price excluding VAT
Spare wheel mounted				€ 182,00
shoring pole car stop				€ 100,00
Remote control (not on TV)				€ 355,00
Extra 5 liter air tank (not on TV)				€ 295,00
Aluminum floor, <b>additional price</b>				At request
Alloy rims, <b>additional price apiece (N)</b>				€ 151,00
"Y" Ratchet strap for car transport				€ 30,00
Double Lock Fixed Lock 'C' SCM, approved by insurers in the Netherlands, mounted				€ 199,00
Winch support				€ 168,00
Winch manual 820kg including 8m <sup>1</sup> winch belt and winch support				€ 375,00
Winch manual 1200kg including 8m <sup>1</sup> winch belt and winch support				€ 430,00
Winch electric 1500kg including winch support				€ 750,00
Winch electric 2000kg with remote control and winch support				€ 970,00
Winch remote control for 1500kg and 2000kg winches				€ 99,00
Hood AA3518, 326x180x180/193, single color PVC cloth, 4x zigzag closing, <b>from</b>				€ 3.025,00
Enclosed body AA3518, 320x180x190cm, 25mm insulated panels, alu. overhead door, <b>from</b>				€ 8.428,00
Technical specifications:				
Make	Tohaco			
Type	AA116/3518	AA118/3518	AA116/3518TV	AA118/3518TV
Chassis	Hot-dip galvanized			
Suspension	Independent, air suspension			
Bed	Fully lowerable for loading and unloading. Ramp angle approx. 5°			
Number of wheels, tire size, rim size	2, 195/50 RC 13C, steel rims 6Jx13H2 5 holes			
Brakes	Knott, mechanic			
Overrun brake	Knott KF20			
Length	4925mm			
Height	1000mm			
Width	2384mm			
Bed length, steel ramp included	3500mm			
Bed width	1800mm			
Bed height	360mm			
Mass roadworthy (depending on equipment)	484kg	501kg	470kg	488kg
Gross weight	1600kg	1800kg	1600kg	1800kg
Load capacity	ca. 1116kg	ca. 1299kg	ca. 1130kg	ca. 1312kg
Maximum nose weight	100kg			
Bed	18mm birch plywood with anti-slip coating			
Jockey wheel	Automatic retractable, galvanized, full rubber wheel			
Plug	13-pin Jaeger plug necessary		13-pin Jaeger plug	
Air suspension system	Electronic		Electric manually	
Ride height and level control	Automatic by sensor		Manually, ride height indicator	
Air tank	Optional 5 liters		n.a.	
Bellows	2			
Shock absorbers	2			
Compressor	12V, 18bar, with moist filter		12V, 10bar	
Valve block	In compressorbox		n.a.	
ASCU (Air Suspension Control Unit)	In compressorbox		n.a.	
Emergency valves	2, left and right			
Mechanical lowering protection	Against unintentional lowering the bed			
Battery	12V, 75Ah, AGM semi traction		12V, 34Ah, AGM semi traction	
Plug for external battery charger	Tohaco			
Wiring harness	Tohaco			
Wiring box	Tohaco		n.a.	
Lighting system	Aspock			
Anchor points	Multiple anchor points in rail, left, right and front			
License plate holder	Collapsible, suited with led-light			